

Standard Unit Specifications



STANDARD BASE UNIT

1450 lbs (659 kgs)

24" Height x 48" Width x 24" Depth (61 H x 122 W x 61 cm D)

Face Area: 8 sq ft (0.745 m²)

Volume of Voids: 6.35 ft³ (.180 m³)



STANDARD UNIT

1450 lbs (659 kgs)

Faces: Varies

Gravel Filled Weight: 2150 lbs (975 kgs)


Batter/Setback: 2.5"-4.5" (depending on face type) 2"/Unit (5 cm / Unit)



STANDARD TOP UNIT

1350 lbs (614 kgs)

Drainage hole for weeping tile connection available upon request. Cut out to attach extender units available upon request.



HALF HIGH BASE UNIT

700 lbs (318 kgs)

12" Height x 48" Width x 24" Depth (30.5 H x 122 W x 61 cm D)

Face Area: 4 sq ft (0.37 m²)

Volume of Voids: 3.15 ft³ (0.09 m³)




HALF HIGH UNIT

700 lbs (318 kgs)

Faces: Varies


Gravel Filled Weight: 1080 lbs (490 kgs)

Batter/Setback: 2.5"-4.5" (depending on face type) 1"/Unit (2.5 cm / Unit)



HALF HIGH TOP UNIT

680 lbs (308 kgs)



STANDARD CORNER/ END UNIT

180 lbs (82 kgs)

24" Height x 26" Top Face Width x
28" Bottom Face Width x 2" Top Narrow
Face x 4" Bottom Narrow Face

(61 H x 66 TFW x 71 BFW x 5 TNF x 10 BNF cm)

Face Area: 4.66 sq ft (0.434 m²)

Faces: Varies



HALF HIGH CORNER/END UNIT

100 lbs (46 lbs)

12" Height x 27" Top Face Width x
28" Bottom Face Width x 3" Top Narrow
Face x 4" Bottom Narrow Face

(61 H x 69 TFW x 71 BFW x 8 TNF x 10 BNF cm)

Face Area: 2.33 sq ft (0.217 m²)

Faces: Varies



STEP/CAP

600 lbs (273 kgs)

6" Height x 48" Width x 24" Depth
(15.25 H x 122 W x 61 cm D)

Face Area: 2 sq ft (.186 m²)